

ABRASION-RESISTANT CORRUGATED SBR SUCTION HOSE



Abrasive suction for crushed rock, sand, dry fertilizer, small gravel and powdered cement. Can also be used as a boom hose for catch basin clean-out. Lightweight, heavy-duty abrasion resistance, -40°F cold-weather resistance, sub-zero flexibility, and a ground wire is not needed as the tube-and-cover compound are static-dissipating.

CONSTRUCTION	Abrasion-resistant SBR tube and cover that are both static-dissipating with a sturdy clockwise helix
TEMPERATURE RANGE	-40° F to 160° F

I.D.	O.D.	WORKING PRESSURE (PSI)	MINIMUM BEND RADIUS	VACUUM (IN/HG)	WEIGHT/FT (LBS)
1 ½"	1.82"	45	2"	29	.37
2"	2.35"	40	2.5"	29	.50
2 ½"	2.95"	35	2.5"	29	.88
3"	3.51"	35	3"	29	1.1
4"	4.63"	30	4.5"	29	1.76
5"	5.75"	30	5"	28	2.47
6"	6.73"	30	9"	28	3.09
8"	9.04"	30	15"	27	5.65

* RAGCO supports the autonomy of its locations to select the best products to service their markets. Subtle variations of these specifications may exist. Contact your RAGCO affiliate for confirmation.