

BLUE PVC LAY-FLAT DISCHARGE HOSE CONTINUED

Pre-coupled, 50' sections coiled for convenient transportation and storage. Available in multiple configurations. Doubled-banded at each end.

ASSEMBLY CHART

COUPLING	I.D. X LENGTH	MAX. W.P. AT 68°F	WEIGHT (EA.)
1 1/2" Pin Lug (M x F)	1 1/2" x 50'	85 psi 5.86 bar	9 lbs
1 1/2" Alum Cam Lock (C x E)	1 1/2" x 50'	85 psi 5.86 bar	9 lbs
1-1/2 polypropylene Cam Lock (C x E)	1-1/2" x 50'	85 psi 5.86 bar	9 lbs
2" Pin Lug (M x F)	2" x 50'	85 psi 5.86 bar	12 lbs
2" Alum Cam Lock (C x E)	2" x 50'	85 psi 5.86 bar	12 lbs
2" Polypropylene Cam Lock (C x E)	2" x 50'	85 psi 5.86 bar	12 lbs
3" Pin Lug (M x F)	3" x 50'	70 psi 4.83 bar	22 lbs
3" Alum Cam Lock (C x E)	3" x 50'	70 psi 4.83 bar	22 lbs
3" Polypropylene Cam Lock (C x E)	3" x 50'	70 psi 4.83 bar	22 lbs

DISCHARGE HOSE WITH CAM & GROOVE ASSEMBLY



DISCHARGE HOSE WITH PIN LUG ASSEMBLY

