

CLEAR PVC SUCTION HOSE



Economical suction hose for water and light chemical applications where inspection of material flow is necessary. Available in FDA food grade.

CONSTRUCTION	Clear PVC w/ white helix
TEMPERATURE RANGE	-10°F to 130°F / -32°C to 85°C

I.D.	O.D.	REC W.P. @ 72° F (PSI)	W.P. @ 149	VACUUM RATING (IN/ HG)	REC MIN BEND RADIUS @ 72° F (INCH)	APPROX BURST PRESSURE @ 72° F (PSI)	APPROX WEIGHT (LBS/ FT)
3/4"	1.02"	100	42	28	2	300	0.21
1"	1.29"	90	42	28	3	300	0.29
1 1/4"	1.84"	90	42	28	4	270	0.38
1 1/2"	1.84"	90	42	28	4	270	0.49
2"	2.39"	70	37	28	5	210	0.71
1 1/2"	2.92"	65	32	28	7	195	0.98
3"	3.46"	55	28	28	8	165	1.28
4"	4.56"	50	28	28	12	150	2.02
5"	5.65"	45	CALL	28	20	135	2.97
6"	6.8"	45	CALL	28	23	135	4.39
8"	8.95"	40	CALL	28	34	120	6.79
10"	11.34"	40	CALL	28	40	120	11.88
12"	13.19"	35	CALL	28	50	105	15.07