



CORRUGATED EPDM SUCTION HOSE

This lightweight, flexible, and durable hose makes for easy handling in irrigation lines, septic service, trash pumps, marine, and irrigation applications. Known as Tigerflex Green or Series 2000. Can be crimped or banded to make assemblies per your specifications.

| | | | |
|---------------------|---------------------------------|--------------------------|------------------|
| CONSTRUCTION | EPDM tube w/ polyethylene helix | TEMPERATURE RANGE | -40° F to 160° F |
|---------------------|---------------------------------|--------------------------|------------------|

| I.D. | O.D. | APPROX W.P. @ 140° F (PSI) | APPROX BURST PRESSURE @ 72° F (PSI) | VACUUM RATING (IN/HG) | REC MIN BEND RADIUS @ 72° F (INCH) | APPROX WEIGHT (LBS/FT) |
|--------|-------|-------------------------------|---|--------------------------|--|---------------------------|
| 1" | 1.34" | 80 | 240 | 28 | 4 | 0.23 |
| 1 1/4" | 1.61" | 70 | 210 | 28 | 5 | 0.3 |
| 1 1/2" | 1.96" | 60 | 180 | 28 | 6 | 0.49 |
| 2" | 2.49" | 60 | 180 | 28 | 9 | 0.69 |
| 2 1/2" | 3" | 50 | 150 | 28 | 11 | 0.91 |
| 3" | 3.6" | 50 | 150 | 28 | 12 | 1.205 |
| 4" | 4.69" | 45 | 135 | 28 | 17 | 1.83 |
| 6" | 6.86" | 35 | 105 | 20 | 17 | 3.84 |

INDUSTRY INTERCHANGE: Tiger-Green, Series 2000, Masterflex 300, 300EPDM