

# DJ MILL HOSE & ASSEMBLIES



## BULK HOSE

A double covered, lightweight, and flexible discharge hose for municipal washdown, hydrant water supply lines, equipment & pump rental, shipyard washdown, and other various discharge applications. Increased abrasion resistance and pressure rating. This economical hose rolls up flat for easy storage and transfer.

<b>TUBE</b>	SBR	<b>TEMPERATURE RANGE</b>	-25°F (-32°C) to 185°F (+85°C)
<b>COVER</b>	Double jacket white polyester	<b>STANDARD LENGTHS</b>	50', 100'

## HOSE CHART

I.D.	SERV. PRESS.	TEST PRESS.	WEIGHT
1 1/2 in	300 psi	600 psi	0.26 lb/ft
38.10 mm	20.68 bar	41.36 bar	0.39 kg/m
2 in	300 psi	600 psi	0.33 lb/ft
50.80 mm	20.68 bar	41.36 bar	0.49 kg/m
2 1/2 in	300 psi	600 psi	0.45 lb/ft
63.50 mm	20.68 bar	41.36 bar	0.67 kg/m

## ASSEMBLIES

All of the same great features and benefits as our bulk hose, and now with the added benefit of coupled assemblies. Couplings are internally expanded, aluminum, hard-coated NPS or NST Male x Female rocker lug. For the transfer of water, wash-down, jetting and irrigation.

## ASSEMBLIES CHART

I.D.	STD LENGTH	THREAD TYPE	WEIGHT
1 1/2 in	50 ft	NPS	15.00 lb/ft
1 1/2 in	50 ft	NST	15.00 lb/ft
2 in	50 ft	NPS	20.00 lb/ft
2 1/2 in	50 ft	NPS	25.00 lb/ft
2 1/2 in	50 ft	NST	25.00 lb/ft



\* RAGCO supports the autonomy of its locations to select the best products to service their markets. Subtle variations of these specifications may exist. Contact your RAGCO affiliate for confirmation.