



GREEN PVC SUCTION HOSE

Economical suction hose for water and light chemical applications. Can be crimped or banded to make assemblies per your specifications.

CONSTRUCTION	Green PVC w/ white helix
TEMPERATURE RANGE	-10°F to 130°F / -32°C to 85°C

I.D.	O.D.	REC W.P. @ 72° F (PSI)	APPROX W.P. @ 140° F (PSI)	VACUUM RATING (IN/ HG)	REC MIN BEND RADIUS @ 72° F (INCH)	APPROX BURST PRESSURE @ 72° F (PSI)	APPROX WEIGHT (LBS/ FT)
3/4"	1.01"	100	42	28	2	300	0.2
1"	1.27"	90	42	28	3	300	0.27
1 1/4"	1.53"	90	42	28	4	270	0.36
1 1/2"	1.82"	90	42	28	5	270	0.47
2"	2.36"	70	37	28	6	210	0.636
2 1/2"	2.98"	65	32	28	8	195	0.92
3"	3.44"	55	28	28	9	165	1.2
4"	4.52"	50	28	28	13	150	1.87
5"	5.65"	45	CALL	28	21	135	3
6"	6.8"	45	CALL	28	24	135	4.56
8"	8.95"	40	CALL	28	35	120	7.05
10"	11.34"	40	CALL	28	41	120	12.37
12"	13.39"	35	CALL	26	53	105	15.66