

# JACKHAMMER HOSE

Rugged four-spiral, with various psi construction, these assemblies can tackle the job that only a jackhammer can dish out. The EPDM tube and cover handle heat, ozone and weather cracking better than other compounds. These hoses are assembled at the factory, crimped with universal (Chicago, CP) fittings at each end. Durability is built in and this hose is ready for hard work. Also available in yellow.



<b>COVER COLOR</b>	Red (also available in yellow)	<b>OIL RESISTANCE</b>	Limited
<b>TUBE MATERIAL</b>	EPDM	<b>COVER MATERIAL</b>	EPDM
<b>REINFORCEMENT</b>	Spiral polyester yarn	<b>TEMPERATURE RANGE</b>	-40°F to +200°F

NOMINAL I.D. (INCHES) (MM)		NOMINAL O.D. (INCHES) (MM)		REINFORCEMENT SPIRALS	WORKING PRESSURE (PSI)	MIN. BEND RADIUS (INCHES) (MM)		WEIGHT (LB/FT) (KG/M)	
3/4	19.05	1.15	29.21			4	200	4.50	114.30
3/4	19.05	1.15	29.21	4	250	4.50	114.30	0.38	0.57
3/4	19.05	1.15	29.21	4	300	4.50	114.30	0.41	0.61
1	25.40	1.37	34.80	4	200	7	177.80	0.51	0.76

**INDUSTRY INTERCHANGE:** Air Power, Sledgehammer