

LOCKING LEVER COUPLINGS

For use with water pumps and irrigation. Locking lever fittings are galvanized quick couplings, each with a double-pin locking lever for smooth closing. Not recommended for use with toxic chemicals. O-Ring is included in all female parts.

FULL VACUUM RATED
30° ARTICULATION
TYPE B INDUSTRIAL
NBR O-RING

LOCK PIN LEVER
INTERCHANGEABLE
GALVANIZED
QUICK AND EASY CONNECTIONS

MALE X FEMALE ASSEMBLY

SIZE	PART #
2"	BGA200
3"	BGA300
4"	BGA400
6"	BGA600
8"	BGA800

MALE X HOSE SHANK

SIZE	PART #
2"	BMS200
3"	BMS300
4"	BMS400
6"	BMS600
8"	BMS800

FEMALE X HOSE SHANK

SIZE	PART #
2"	BFS200
3"	BFS300
4"	BFS400
6"	BFS600
8"	BFS800



* RAGCO supports the autonomy of its locations to select the best products to service their markets. Subtle variations of these specifications may exist. Contact your RAGCO affiliate for confirmation.

LOCKING LEVER COUPLINGS CONTINUED

MALE X MALE THREAD

SIZE	PART #
2"	BMT200
3"	BMT300
4"	BMT400
6"	BMT600
8"	BMT800



FEMALE X MALE THREAD

SIZE	PART #
2"	BFT200
3"	BFT300
4"	BFT400
6"	BFT600
8"	BGT800



MALE X 150# FLANGE

SIZE	PART #
4"	BMF400
6"	BMF600
8"	BMF800



FEMALE X 150# FLANGE

SIZE	PART #
4"	BFF400
6"	BFF600
8"	BFF800



LOCKING LEVER

SIZE	PART #
2"	BLR200
3"	BLR300
4"	BLR400
6"	BLR600
8"	BLR800



O-RING

SIZE	PART #
2"	BOR200
3"	BOR300
4"	BOR400
6"	BOR600
8"	BOR800

