

PIN-LUG COUPLINGS

Also called "suction hose couplings," these are threaded couplings used for suction or discharge of water or other fluids. Standard threading is NPSM (National Pipe Straight Mechanical). 1-1/2" and 2-1/2" are available in NST thread (American National Fire Hose Straight Thread). NST does not interchange. Pin lugs are on all sizes of the female end. Sizes 2-1/2" through 6" also have pin lugs on the male end. Fittings seal on a washer that sits in the female end. Replacement washers are available.

PIN-LUG COUPLING SETS

SIZE	THREAD	ALUMINUM W/ BRASS SWIVEL	BRASS W/ BRASS SWIVEL
1 1/2"	NPSM	AB150	BR150
1 1/2"	NST	AB150NST	BR150NST
2"	NPSM	AB200	BR200
2 1/2"	NPSM	AB250	BR250
2 1/2"	NST	AB250NST	BR250NST
3"	NPSM	AB300	BR300
4"	NPSM	AB400	BR400
6"	NPSM	AB600	BR600



WASHERS FOR PIN LUGS

SIZE	PART #
1 1/2"	RW150
1 1/2" NST	RW150NST
2"	RW200
2 1/2"	RW250
2 1/2" NST	RW250NST
3"	RW300
4"	RW400
6"	RW600

