



STANDARD O-RING CORD

NOMINAL CROSS SECTION (IN)	ACTUAL CROSS SECTION (IN)	TOLERANCE (IN)
1/16	0.063	0.005
1/16	0.070	0.007
3/32	0.093	0.007
3/32	0.103	0.007
1/8	0.125	0.007
1/8	0.139	0.007
3/16	0.188	0.007
3/16	0.210	0.007
1/4	0.250	0.008
1/4	0.275	0.008
5/16	0.313	0.008
3/8	0.375	0.010
7/16	0.437	0.012
1/2	0.500	0.015
9/16	0.562	0.015
5/8	0.625	0.015
3/4	0.750	0.015
7/8	0.875	0.020
1	1.000	0.020
1 1/16	1.062	0.030
1 1/8	1.125	0.030
1 1/4	1.250	0.040
1 1/2	1.500	0.060

METRIC O-RING CORD

DIAMETER (MM)	DIAMETER (IN)	TOLERANCE (MM)
2.0	0.079	+/- 0.10
2.5	0.098	+/- 0.10
3.0	0.118	+/- 0.12
3.5	0.139	+/- 0.15
4.0	0.158	+/- 0.15
4.5	0.177	+/- 0.15
5.0	0.197	+/- 0.20
5.7	0.224	+/- 0.25
6.0	0.236	+/- 0.25
7.0	0.275	+/- 0.25
7.5	0.295	+/- 0.25
8.4	0.330	+/- 0.25
9.0	0.354	+/- 0.25
10.0	0.393	+/- 0.25
12.0	0.472	+/- 0.45
14.0	0.550	+/- 0.50