



SJ HOSE & ASSEMBLIES

Heavy-duty, but lightweight synthetic cover for better abrasion resistance and abuse. Higher working pressures. For water discharge service in rental yards, fleet service, municipal wash-down, utility dewatering. Available in bulk hose, standard and custom assemblies.

TUBE	SBR	TEMPERATURE RANGE	-25°F to 185°F
COVER	White polyester jacket	STANDARD LENGTHS	50', 100'

HOSE CHART

I.D.	CPLNG. BOWL	SERV. PRESS.	WEIGHT
1 1/2 in	1.81 in	230 psi	0.23 lb/ft
2 in	2.31 in	230 psi	0.28 lb/ft
2 1/2 in	2.81 in	200 psi	0.39 lb/ft
3 in	3.38 in	200 psi	0.50 lb/ft
4 in	4.38 in	200 psi	0.66 lb/ft

ASSEMBLIES CHART

I.D.	LENGTH	COUPLING	WEIGHT
1 1/2 in	50FT	Pin Lug	15 lbs
1 1/2 in	50FT	C x E	15 lbs
2 in	50FT	Pin Lug	19 lbs
2 in	50FT	C x E	19 lbs
3 in	50FT	Pin Lug	22 lbs
3 in	50FT	C x E	22 lbs

PIN LUG ASSEMBLY



CAMLOCK ASSEMBLY

